### DATASHEET ISSUE 1 – JAN 2020



Plumbing & Drainage



## StormCrate55 **Cellular Storm Water Crate**

Brett Martin's StormCrate55 modular cellular crates are used in storm water retention, attenuation and infiltration applications. The crates are designed to be simply and easily stacked together to create a below ground storm water holding tank or to allow the infiltration of storm water into the ground around them. The void created by the crates can then fill up with storm water during heavy rainfall conditions. The collected storm water then drains away slowly into the drainage system when the crate is used for attenuation, or, soaks away slowly into ground water table when the crate is used for infiltration.

#### **APPLICATIONS**

- Landscaped areas
- Pedestrianised areas
- Public open spaces
- Playgrounds
- Parking areas
- Driveways
- Access areas

#### **KEY BENEFITS**

- Load bearing strength of 562kN per m<sup>2</sup>
- Ideal for retention, attenuation or infiltration applications with a suitable geomembrane or geotextile
- Designed for trafficked and untrafficked areas\*
- Integrated inlet and outlet
- 4 StormCrates per 1m<sup>3</sup>
- 95% void ratio
- 100% recyclable

#### **TECHNICAL SUPPORT**

Installation guidance and assistance is available. For further information, please call 01246 280000 or email building@ brettmartin.com

#### PRODUCT COMPONENTS



SHEAR PIN CONNECTOR Code B8252 (2 INCLUDED)



# STORMCRATE55 CONNECTOR Code B8251 (4 INCLUDED)

\*Depending on installation conditions. Refer to the Installation and Design Guide or contact the Technical Department.

Brett Martin Plumbing & Drainage (Ireland Sales) 24 Roughfort Road, Newtownabbey, Co. Antrim, BT36 4RB, UK Tel: +44 (0) 28 9084 9999 Fax: +44 (0) 28 9083 6666 Email: sales@brettmartin.com

Brett Martin Plumbing & Drainage (GB Sales) Speedwell Industrial Estate, Staveley, Derbyshire S43 3JP Tel: +44 (0) 1246 280000 Fax: +44 (0) 1246 280001 Email: building@brettmartin.com



#### www.brettmartin.com

All reasonable care has been taken in the compilation of the information contained within this literature. All recommendations on the use of our products are made without guarantee as conditions of use are beyond the control of Brett Martin. It is the customer's responsibility to ensure that the product is fit for its intended purpose and that the actual conditions of use are suitable. Brett Martin pursues a policy of continuous product development and reserves the right to amend specifications without prior notice. StormCrate55 is a registered trademark of Brett Martin Ltd. Brett Martin Ltd.'s Normal Conditions of Sale apply.

| PROPERTIES          | VALUE                  |                             |
|---------------------|------------------------|-----------------------------|
| PHYSICAL PROPERTIES |                        |                             |
| Volume              | 0.25m <sup>3</sup>     |                             |
| Cube Storage Volume | 0.2375m <sup>3</sup>   |                             |
| Void Ratio          | 95%                    |                             |
| Dimensions          | 1200mm x 600mm x 347mm |                             |
| Connections         | 12 × pipe inlets       |                             |
| Weight              | 15.5kg                 |                             |
| Material            | Polypropylene          |                             |
| STRENGTH            | VERTICAL               | LATERAL                     |
| Short Term Strength | 562kN/m <sup>2</sup>   | <b>70</b> kN/m <sup>2</sup> |
| Long term Strength  | 153kN/m <sup>2</sup>   | <b>19</b> kN/m <sup>2</sup> |



